



39.95 EUR

incl. 19% VAT, plus [shipping](#)

- Wireless video !



2.4GHZ wireless rear view and reversing camera system (max. distance 5-10m). The mini camera transmits a live image to the viewing monitor, normally located on your dashboard (eg. CTFPND-1 V4/V5). License plate car rear view camera, 120 degree wide angle with wide picture. Low illumination, 3 meter IR range. Waterproof level: IP65. Great for CARS, VANS, RACE TRUCKS, LORRIES, HORSE BOXES, TRAILERS, etc...

CTFPND-1 V4/V5 switches automatically to the camera picture as soon as the camera is powered on.

CTFPND-1 V5: Proper connection while using together with TMC receiver: Power adapter -> camera receiver -> TMC-receiver -> PND.

|                        |                                      |
|------------------------|--------------------------------------|
| Video system           | PAL/NTSC                             |
| Pixel                  | PAL 628x586<br>NTSC 510x496          |
| CMOS                   | 1/3" OmmVision CMOS                  |
| Minimum Illumination   | 3.0 Lux (F 1.2)                      |
| Scanning Frequency (H) | 15.625KHz(PAL), NTSC:15.734KHz(NTSC) |
| Scanning Frequency (V) | 50Hz(PAL), 60Hz(NTSC)                |
| Power                  | DC 12V                               |

|                        |                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------|
| Receiving Sensitivity  | < -8.5dBm                                                                                                 |
| Video Output           | 1 Vp-p 75, S/N>38dB                                                                                       |
| <b>Receiver</b>        |                                                                                                           |
| Power                  | 5V DC (via USB)                                                                                           |
| Modulation Mode        | FM                                                                                                        |
| Transmission Frequency | ISM 2400~2483Mhz                                                                                          |
| Connectors             | 2x Mini-USB (for 5V power), 2.5mm jack (for video)                                                        |
| <b>Sender</b>          |                                                                                                           |
| Power                  | 12V DC                                                                                                    |
| Modulation Mode        | FM                                                                                                        |
| Transmission Frequency | ISM 2400~2483Mhz                                                                                          |
| Connectors             | 12V (for connecting to vehicle rear light), GND                                                           |
| <b>Scope of supply</b> | - NOTE : The 7" PND device (CTFPND-1 V4) visible on the product photo is not included in scope of supply. |
|                        | - Camera (width : 25cm)                                                                                   |
|                        | - Sender unit                                                                                             |
|                        | - receiver unit                                                                                           |