

999.00 EUR
incl. 19% VAT, plus shipping

- Intel® Q67 Express Chipset
- Supports Intel LGA 1155 Socket Core™ i3, i5, i7 & Pentium Processors
- Support 4 * 240 pin 4GB 1333/1066 Dual CH DDR3 SDRAM DIMM Max. up to 32GB
- Intel 82579LM & 82574L Gigabit LAN
- Intel Active Management Technology (iAMT 7.0)
- Support TPM 1.2 function
- Support CPU Smart FAN
- Supports ACPI S3 Function
- Support Watch dog Technology
- ATX form factor 305mm x 244mm

• **CPU**	INTEL® LGA 1155 Socket Core i7/i5/i3/Pentium Processor
• **Chipset**	INTEL® Q67 Chipset Clock 100MHz
• **Memory**	4 * 240 pin 4GB 1333/1066 Dual CH DDR3 SDRAM DIMM Max. up to 32GB
• **Expansion Slots**	1 *PCIe x 16, 4 * PCI, 1 * PCIe x 1, 1 * PCIe x 4 1 * MINI PCI-E & 1 * mSATA socket
• **Storage**	2 * Serial ATA3 6Gb/s & 3 * Serial ATA2 3Gb/s connectors support RAID 0, 1, 5, 10
• **Audio**	VIA VT1705 6-Channel HD Audio CODEC
• **Ethernet LAN**	Intel 82579LM & 82574L PCI-E Gigabit Ethernet LAN
• **USB**	Embedded 12 * USB 2.0/1.1

• **Special Features**	Support ACPI S3 Support CPU Smart FAN Support Watch Dog
• **Rear Panel I / O**	6 * USB 2.0/1.1 ports 1 * PS2/KB Connector 2 * RJ-45 port 1 * HDMI port 1 * COM port 1 * VGA port 3 * Audio Phone Jack
• **Internal I / O**	3 * USB 2.0/1.1 headers for 6 USB 2.0 ports CPU /NB / Chassis Fan connectors 1 * Parallel header 1 * GPIO header 9 * COM header (COM2 for RS232/422/485) 1 * TPM 1.2 header 1 * IR header 1 * Chassis Intrusion header 1 * AUDIO header 1 * 24-pin & 8-pin 12V ATX Power connector
• **BIOS**	AMI EFI 64MB SMT Flash ROM
• **Form Factor**	ATX form factor■305mm x 244mm■
• **Functional**	ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
• **Certificate**	CE, FCC, RoHS
• **Temperature**	Operating within 0~60 centigrade Storage within -20-85 centigrade